

AMENDMENT(S) TO THE CLAIMS

1. (Original) A sprinkler, comprising:
an outer housing having a lower end connectable to a source of pressurized water;
a riser vertically reciprocable along a vertical axis within the outer housing between
extended and retracted positions when the source of pressurized water is turned ON and OFF;
a nozzle mounted at an upper end of the riser for rotation about the vertical axis;
a turbine mounted inside the riser for rotation about a horizontal axis; and
a drive mechanism connecting the turbine to the nozzle so that when the source of
pressurized water is turned ON the resulting rotation of the turbine by the pressurized water will
rotate the nozzle.

2. (Original) The sprinkler of Claim 1 wherein the drive mechanism includes a
reversing mechanism for causing the nozzle to rotate between a pair of arc limits.

3. (Original) The sprinkler of Claim 1 and further comprising a mechanism that
allows a least one of the arc limits to be adjusted.

4. (Previously Amended) The sprinkler of Claim 1 wherein the turbine includes a
disk and a plurality of equally circumferentially spaced cups formed on the periphery of the disk.

5. (Original) The sprinkler of Claim 1 wherein the turbine and a drive mechanism
that connects the turbine to the nozzle are mounted inside a pair of clam-shell case members
inside the riser.

6. (Original) The sprinkler of Claim 5 wherein the drive mechanism includes a gear
train reduction including a plurality of gears that rotate about a plurality of corresponding
horizontal axes.

7. (Original) The sprinkler of Claim 5 wherein at least one of the case members
2 defines a water inlet.

8. (Original) The sprinkler of Claim 1 and further comprising a manually adjustable
2 stator for varying a rotational speed of the turbine.

9. (Original) The sprinkler of Claim 1 and further comprising a first filter for
2 straining all water flowing into the lower end of the outer housing and a second filter for straining
a portion of the water flowing past the turbine.

10. (Original) The sprinkler of Claim 5 wherein the drive mechanism includes a
2 reversing mechanism mounted inside the claim-shell case members that causes the nozzle to
rotate between a pair of arc limits.

11. (Once Amended) A sprinkler, comprising:
2 an outer housing having a lower end connectable to a source of pressurized water;
a riser vertically reciprocable along a vertical axis within the outer housing between
4 extended and retracted positions when the source of pressurized water is turned ON and OFF;
a nozzle mounted at an upper end of the riser for rotation about the vertical axis;
6 a plurality of mating case members dimensioned to fit inside the riser;
a turbine entirely mounted inside the case members; and
8 a drive mechanism mounted inside the case members that connects the turbine to the
nozzle so that when the source of pressurized water is turned ON the resulting rotation of the
10 turbine by the pressurized water will rotate the nozzle.

12. (Original) The sprinkler of Claim 11 wherein the drive mechanism includes a
2 reversing mechanism for causing the nozzle to rotate between a pair of arc limits.

13. (Original) The sprinkler of Claim 11 and further comprising a mechanism that
2 allows a least one of the arc limits to be adjusted.

14. (Previously Amended) The sprinkler of Claim 11 wherein the turbine includes a disk and a plurality of equally circumferentially spaced cups formed on the periphery of the disk.

15. (Original) The sprinkler of Claim 11 wherein the turbine rotates about a horizontal axis.

16. (Original) The sprinkler of Claim 11 wherein the drive mechanism includes a gear train reduction including a plurality of gears that rotate about a plurality of corresponding horizontal axes.

17. (Original) The sprinkler of Claim 11 wherein at least one of the case members defines a water inlet.

18. (Original) The sprinkler of Claim 11 and further comprising a manually adjustable stator for varying a rotational speed of the turbine.

19. (Original) The sprinkler of Claim 11 and further comprising a first filter for straining all water flowing into the lower end of the outer housing and a second filter for straining a portion of the water flowing past the turbine.

20. (Original) A sprinkler, comprising:
an outer housing having a lower end connectable to a source of pressurized water;
a riser vertically reciprocable along a vertical axis within the outer housing between extended and retracted positions when the source of pressurized water is turned ON and OFF;
a nozzle mounted at an upper end of the riser for rotation about the vertical axis;
a plurality of mating case members dimensioned to fit inside the riser, at least one of the case members defining a water inlet and a water outlet;
a turbine mounted inside the case members receiving water passing through the inlet for powered rotation about a first horizontal axis;

10 a drive mechanism mounted inside the case members that connects the turbine to the
nozzle so that when the source of pressurized water is turned ON the resulting rotation of the
12 turbine by the pressurized water will rotate the nozzle, the drive mechanism including a gear
train reduction having a plurality of gears that rotate about a plurality of corresponding second
14 horizontal axes and a reversing mechanism for causing the nozzle to rotate between a pair of arc
limits; and
16 a manually adjustable stator for varying a rotational speed of the turbine.

21-24. (Canceled)

25. (Original) The sprinkler of Claim 21 wherein the turbine rotates about a horizontal
2 axis.

26. (Original) The sprinkler of Claim 21 wherein the drive mechanism includes a gear
2 train reduction including a plurality of gears that rotate about a plurality of corresponding
horizontal axes.

27. (Canceled)

28. (Original) The sprinkler of Claim 21 and further comprising a manually adjustable
2 stator for varying a rotational speed of the turbine.

29. (Original) The sprinkler of Claim 21 wherein the drive subassembly includes a
2 pair of mating case members that enclose the turbine and the drive mechanism.

30. (Canceled)